



# JHFH、JHFHS-重载螺钉



编码规则

JHFH - M8 - 12 - ZI  
 JHFH S - 0420 - 15  
 ↓ ↓ ↓ ↓ ↓  
 类 材 螺 长 表  
 型 料 纹 度 面  
 代 代 代 代 处  
 码 码 码 码 理



公制尺寸 (单位: 毫米 mm)

螺纹规格	螺钉类型		螺纹代码	最小板厚	安装孔直径 +0.13	长度代码“L” ±0.4 (长度代码以毫米为单位)					H ±0.25	S 最大	T 最大	最小孔边距
	碳钢	不锈钢				.75	1.00	1.25	1.50	1.75				
M5 x 0.8	JHFH	JHFHS	M5	1.3	5	15	20	25	30	35	7.8	2.7	1.14	10.7
M6 X 1	JHFH	JHFHS	M6	1.5	6	15	20	25	30	35	9.4	2.8	1.27	11.5
M8x1.25	JHFH	JHFHS	M8	2	8	15	20	25	30	35	12.5	3.5	1.78	12.7
M10x1.5	JHFH	JHFHS	M10	2.3	10	15	20	25	30	35	15.70	4.1	2.29	13.7

英制尺寸 (单位: 英寸 in)

螺纹规格	螺钉类型		螺纹代码	最小板厚	安装孔直径 +.005	长度代码“L” ±.015 (长度代码以 1/16 英寸为单位)					H ±.010	S 最大	T 最大	最小孔边距
	碳钢	不锈钢				.75	1.00	1.25	1.50	1.75				
10#-32	JHFH	JHFHS	032	.050	.190	12	16	20	24	28	.300	.105	.040	.415
1/4-20	JHFH	JHFHS	0420	.060	.250	12	16	20	24	28	.380	.125	.050	.460
5/16-18	JHFH	JHFHS	0518	.075	.312	12	16	20	24	28	.480	.140	.070	.500
3/8-16	JHFH	JHFHS	0616	.090	.375	12	16	20	24	28	.580	.155	.085	.530

性能参数-JHFH/JHFHS -重载螺钉

公 制	螺钉类型	螺纹代码	螺母扭矩最大 N. m	安装板 厚度及材质	安装板硬度 HRB	安装力 KN	推出力 N	扭出力 N. m	抗拉强度 KN
	JHFH	M5	7.7	1.5mm 铝	15	13	800	5.4	12.8
	JHFH	M6	13	1.5mm 铝	43	29	1270	14	18.1
	JHFH	M8	32	2.3mm 铝	39	35.6	1700	30	32.9
	JHFH	M10	63	2.3mm 铝	39	53.3	2445	36	52.2
	JHFH	M5	7.7	1.5mm 钢	65	26	1500	7.6	12.8
	JHFH	M6	13	1.5mm 钢	59	33	1750	14	18.1
	JHFH	M8	32	2.3mm 钢	58	44.5	2200	30	32.9
	JHFH	M10	63	2.3mm 钢	58	71.2	3470	49	52.2
	JHFHS	M5	3.8	1.62mm 铝	35	12.4	800	5.4	7.3
	JHFHS	M6	6.5	1.62mm 铝	35	15.4	1270	11	10.3
	JHFHS	M8	16	2.23mm 铝	44	24.4	1700	20	18.8
	JHFHS	M10	31	2.3mm 铝	44	44.4	2445	36	29.9
	JHFHS	M5	3.8	1.47mm 钢	54	21.7	1500	6.4	7.3
	JHFHS	M6	6.5	1.6mm 钢	45	24.6	1750	11	10.3
JHFHS	M8	16	2.48mm 钢	43	37.8	2100	20	18.8	
JHFHS	M10	31	2.3mm 钢	44	57.7	3470	36	29.9	
JHFH	M5	6.4	1mm HC500LA	89	51.1	1350	8.1	12.8	
JHFH	M6	11	1mm HC500LA	89	60	1400	14.4	18.1	
JHFHS	M8	26	1.5mm HC500LA	91	71.7	2400	33.9	32.9	

英 制	螺钉类型	螺纹代码	螺母扭矩最大 ft. lbs.	安装板 厚度及材质	安装板硬度 HRB	安装力 lbs.	推出力 lbs.	扭出力 ft. lbs.	抗拉强度 lbs.
	JHFH	032	4.6	.060" 铝	15	3000	180	4	2400
	JHFH	0420	9.6	.060" 铝	43	5500	285	11	3820
	JHFH	0518	20	.091" 铝	39	8000	380	22	6280
	JHFH	0616	35	.091" 铝	39	12000	550	25	9300
	JHFH	032	4.6	.060" 钢	65	6000	375	5	2400
	JHFH	0420	9.6	.060" 钢	59	7000	480	11	3820
	JHFH	0518	20	.090" 钢	58	10000	590	22	6280
	JHFH	0616	35	.090" 钢	58	16000	780	36	9300
	JHFHS	032	2.5	.050" 铝	38	4000	180	4	1500
	JHFHS	0420	5.2	.064" 铝	32	4000	285	8	2385
	JHFHS	0518	11	.087" 铝	41	5500	380	15	3930
	JHFHS	0616	19	.123" 铝	44	10000	560	25	5810
	JHFHS	032	2.5	.058" 钢	52	4500	325	4	1500
	JHFHS	0420	5.2	.072" 钢	43	6500	480	8	2385
	JHFHS	0518	11	.099" 钢	44	7500	590	15	3930
	JHFHS	0616	19	.099" 钢	44	13000	780	25	5810
	JHFH	032	4.2	.040" HC500LA	89	9500	300	60	2400
	JHFH	0420	10	.040" HC500LA	89	13500	340	130	3820
	JHFHS	0518	23	.060" HC500LA	91	16000	575	290	6280